

# 2015-I UP-SHINE LED CEILING LIGHT SERIES



## AL08

10" / 12" / 14"



### Technical Specifications

Voltage: AC100-240V / AC200-240V  
 Power: 12W / 18W / 25W  
 Power Factor:  $\geq 0.9$   
 Beam angle: 120°  
 CCT: 3000K 4000K 5000K 5700K

Lifespan: 40000hrs  
 CRI:  $\geq 80$   
 IP: 54  
 Dimmable: Triac dimmable  
 Surface color: White

Model	Non-DIM Lumen ( $\pm 5\%$ )				DIM Lumen ( $\pm 5\%$ )			
	3000K	4000K	5000K	5700K	3000K	4000K	5000K	5700K
UP-AL08-10-12W	996	1056	1068	1020	996	1056	1068	1020
UP-AL08-12-18W	1530	1620	1620	1620	1530	1620	1620	1620
UP-AL08-14-25W	2075	2150	2200	2125	2075	2150	2200	2125

### Emergency & Sensor induction

Model: UP-AL08-10-12W  
 Power: 12W  
 Emergency power: 4W  
 Emergency time: 3 hrs

Charging time: 24 hrs  
 Induction distance: 5m-8m  
 Induction time delay: 30sec  
 Induction methods: Human body by microwave induction

Model	Normal Lumen ( $\pm 5\%$ )				Emergency Lumen ( $\pm 5\%$ )			
	3000K	4000K	5000K	5700K	3000K	4000K	5000K	5700K
UP-AL08-10-12W	996	1056	1068	1020	332	352	356	340



## Up-shine Lighting Co., Limited

地址：广东省深圳市宝安区福永街道福园一路鼎丰高新产业园 2 栋  
 2nd building Dingfeng High-Tech Zone, Fuyuan 1st road,  
 Fuyong Sub-district, Bao'an, Shenzhen China  
 Tel: +86-755-29197332  
 Fax: +86-755-29197301  
 E-mail: info@upshine-lighting.com  
 Web: www.upshine.com  
 Zip code: 518103



## Three colors in one LED AL08-P

10" / 12"



### Technical Specifications

Voltage: AC200-240V  
Power: 12W / 18W  
Power Factor:  $\geq 0.9$   
Beam angle: 120°  
CCT: 3000K 4000K 5700K

Lifespan: 40000hrs  
CRI:  $\geq 80$   
IP: 54  
Dimmable: Triac dimmable  
Surface color: White

Model	DIM Lumen ( $\pm 5\%$ )		
	3000K	4000K	5700K
UP-AL08-10-12W-P	996	1056	1020
UP-AL08-12-18W-P	1530	1620	1620

## AL12 12"



### Technical Specifications

Voltage: AC100-240V / AC200-240V  
Power: 18W  
Power Factor:  $\geq 0.9$   
Beam angle: 120°  
CCT: 3000K 4000K 5700K

Lifespan: 40000hrs  
CRI:  $\geq 80$   
IP: 54  
Dimmable: Triac dimmable  
Surface color: White

Model	Non-DIM Lumen ( $\pm 5\%$ )				DIM Lumen ( $\pm 5\%$ )			
	3000K	4000K	5000K	5700K	3000K	4000K	5000K	5700K
UP-AL12-12-18W	1494	1584	1602	1512	1494	1584	1602	1512

## AL02 11" / 14"



AL02-A  
Ø275x100mm (15W)  
Ø350x110mm (25W)



AL02-B  
Ø300x86mm (15W)  
Ø350x96mm (25W)



### Technical Specifications

Voltage: AC100-240V / AC100-130V AC200-240V  
Power: 15W / 25W  
Power Factor:  $\geq 0.9$   
Beam angle: 120°  
CCT: 3000K 4000K 5000K 5700K

Lifespan: 40000hrs  
CRI:  $\geq 80$   
IP: 20  
Dimmable: Triac dimmable  
Surface color: White / Brush nickel

Model	Non-DIM Lumen ( $\pm 5\%$ )				DIM Lumen ( $\pm 5\%$ )			
	3000K	4000K	5000K	5700K	3000K	4000K	5000K	5700K
UP-AL02-11-15W-A	1050	1170	1220	1240	1000	1100	1160	1180
UP-AL02-11-15W-B	1000	1080	1130	1150	960	1030	1080	1100
UP-AL02-14-25W-A	1870	2000	2050	2120	1740	1860	1900	1970
UP-AL02-14-25W-B	1480	1620	1650	1680	1340	1460	1500	1520